



PLATINUM
SAFES

THE DOCO

FIRE RESISTANT SAFE



Certified Fire Resistance

The Doco offers SP Certified 90-120 minutes fire resistance. A higher level of fire protection than most safes to protect important documents, files and belongings. The Doco is ideal for both residential and commercial use.

Safes have the option of being supplied on heavy-duty casters for convenience. Fitted with a dual digital & key locking device adds additional security and protection.



Certified Safes



Recommended
Cash Rating \$ 5,000



90 minutes fire rating
Model 610, 670, 750,
880, 1750



120 minutes fire rating
Model 1000, 1200,
1400, 1600



Warranty:
5 years on safe
2 years on construction



Features

- ◆ **SP CERTIFIED NT FIRE 017 – 120 PAPER 2 Hours Fire Resistance**
Models 1000, 1200, 1400, 1600
- ◆ **SP CERTIFIED NT FIRE 017 – 90 PAPER 90 Minutes Fire Resistance**
Models 610, 670, 750, 880, 1750
- ◆ **Asbestos tested and checked**
- ◆ Recommended Cash Rating \$ 5,000 (unsupported)
- ◆ Fully insulated body and door with fire resistant materials
- ◆ Total body thickness 85mm and door thickness 55mm
- ◆ 3 way locking mechanism on models 750 and up
- ◆ 25mm locking bolts. Adjustable shelving
- ◆ Features one internal key locking drawer 140mm high (excluding 610).
Drawer positioned above on models 670, 750, 880, 1000. Drawer positioned below on models 1200, 1400, 1600.
- ◆ Features two internal key locking drawers 140mm high positioned below on model 1750
- ◆ Model 610 features a pull out tray (not lockable)
- ◆ Fitted with dual locking digital and key lock (work independently)
- ◆ Unit can be supplied with or without wheels (70mm wheel height included in external height)
- ◆ Durable white paint finish
- ◆ 5 years warranty on safe and 2 years on locks



Dual Digital & Key Locking Mechanism



Internal Lockable Drawer/s



Specifications

Model	External (mm)			Internal (mm)			Litre Capacity	Weight	Shelves	Drawers
	Height	Width	Depth	Height	Width	Depth				
DC-610	622	462	466	422	322	310	42	90	1	1
DC-670	610	500	470	470	360	317	52	105	1	1
DC-750	690	530	510	550	390	352	74	140	1	1
DC-880	880	590	505	666	446	345	102	180	2	1
DC-1000	1000	600	530	776	446	360	125	210	2	1
DC-1200	1185	700	630	945	530	460	230	270	2	1
DC-1400	1385	700	630	1145	530	460	280	335	3	1
DC-1600	1585	800	630	1345	630	460	390	425	3	1
DC-1750	1700	1150	630	1445	980	460	651	735	3	2

- 70mm Wheel height included in external height in table
- Add 50mm to depth for door handle projection

Distributed by: